

## HOSE 2 GO H2GO

### Constant pressure water supply unit without a battery or pump

THE HOSE 2 GO provides a consistent flow of water that allows for both cooling and dust suppression when cutting, core drilling and grinding concrete. Once the user has filled the unit from a tap it's ready to go, giving the user up to 30 minutes of constant flowing water without using a battery or pump.

#### CHALLENGE ON THE JOB?

- Getting a constant flow of water for dust suppression
- Tanks being too heavy to move around
- Tanks breaking down
- Running out of battery power
- Limited availability of on site water supply

#### **SPECIFICATIONS**

Length 325mm/12.8in Width Height (placed horizontally) Weight (Dry) Weight (Full) Full tank capacity

144mm/5.7in 800mm/31.5in 5.7kg/12.6 lb 19.5kg/43 lb 13.8L/3.65 gal

#### **SOLUTIONS**

- No pump which means greater reliability
- No complicated electrics to breakdown
- No need to manually pump for water pressure you need
- On the job dust suppression easy and simple
- Up to 30 mins constant flow of water
- Portable only weighs 20kg (44lb) so you can use it anywhere
- On the job cooling ensuring longer blade life



13.8 (3.6 gal) of water 🗸 litre capacity 🗸



Usage up to 30 mins

Cutting, washing or drilling, the Hose 2 Go provides a water supply without the need to manually pump to maintain pressure.





Carry the Hose 2 Go to job site with the strap attachment





Easily portable, just fill up at the tap and go.

# MAKINE

#### ACCESSORIES



1. Spray Guns



2. Hose 3m



3. Tap Adaptor



4. Screw on quick connect hose fitting



5. Quick connect stop valve hose fitting



6. Strap attachment

Please refer to page 27 for part numbers